

INDUSTRIAL COMPONENT DATA

FL SWITCH 4824E-4GC 2891072 PHOENIX CONTACT

Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 4824E-4GC



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 4824E-4GC
Catalog number	2891072
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-891AD0F853
Generated	2026-08-04

Product Overview

Industrial Ethernet Switch

IEC 61850 and IEEE 1613 managed switches for 19" rack mounting. Equipped with 24 RJ45 ports for 10/100 MBits/s and 4 Gigabit-Combo ports (10/100/1000 MBits/s in RJ45 connection; 1000 MBits/s fiber optic connection requires a 1000 MBits/s SFP module).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > I/O**

Additional Product Information

Key Commercial Data

Orderkey 2891072

Packing unit 1 pc

Catalog page Page 428 (C-6-2017)

GTIN 4046356764360

Weight per Piece (excluding packing) 4,470.000 g

Custom tariff number 85176200

Country of origin TW (Taiwan)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 442 mm

Height 44 mm

Depth 375 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Air pressure (storage/transport) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 24 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Ethernet in RJ45 twisted pair

Transmission speed 10/100 Mbps

Transmission length 100 m

Interface 3 Ethernet (RJ45/FO combo)

No. of ports 4

Connection method Combo

Note on the connection method Auto negotiation and autocrossing (RJ45 interface)

Transmission physics Ethernet RJ45 (10/100/1000 Mbps) or SFP (1000 Mbps)

Transmission speed 10/100/1000 Mbps

Function

Basic functions Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 4824E-4GC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.