

INDUSTRIAL COMPONENT DATA

FMCD 1,5/ 4-ST-3,5 YE 1707229 PHOENIX CONTACT Plug-in part, rated current: 8 A, number of poles: 4, pitch: 3..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FMCD 1,5/ 4-ST-3,5 YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	FMCD 1,5/ 4-ST-3,5 YE
Catalog number	1707229
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-24FEE55D7C
Generated	2026-08-05

Product Overview

Plug-in part, rated current: 8 A, number of poles: 4, pitch: 3.5 mm, connection type: Push-in spring connection, color: yellow, contact surface: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: yellow, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 8, number of rows: 2, number of poles: 4, number of connections: 8, article family: FMCD 1.5/.. -ST, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 8 A, number of positions: 4, pitch: 3.5 mm, connection method: Push-in spring connection, color: yellow, contact surface: Tin

Key Commercial Data

Orderkey 1707229

Packing unit 1

GTIN 4046356903318

Custom tariff number 85366990

General

Range of articles FMCD 1,5/..-ST

Type of contact Female connector

Number of positions 4

Connection method Push-in spring connection

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

eCI@ss

eCI@ss 5.1 27141190

eCI@ss 6.0 27260704

eCI@ss 8.0 27440309

eCI@ss 9.0 27440309

ETIM

ETIM 5.0 EC002638

ETIM 6.0 EC002638

UNSPSC

UNSPSC 13.2 39121409

ETIM for 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FMCD 1,5/ 4-ST-3,5 YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.