

INDUSTRIAL COMPONENT DATA

HC-26S1N8A6300 1623272 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-26S1N8A6300



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-26S1N8A6300
Catalog number	1623272
Category	Sensor-actuator connector chassis
Minimum order	24 Pcs
Document ID	EO-083C714C82
Generated	2026-08-04

Product Overview

Device connector, front mounting

Conect. plug. to be apar. front wall, straight, Screw lock, M27, number of poles: 26, contact type: Female, Axial O-ring, Central fixing, shielded: yes, protection index: IP67, plugged in state, number of poles: 26, connection type: Crimped connection, series: HC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1623272

Packing unit 1

GTIN 4055626272962

Custom tariff number 85366990

General

Note Order information: Order crimp contacts Ø 1 mm separately

Type of locking Screw locking

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Number of positions 26
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Pg housing screw connection none
Mounting type Central fixing
Ambient conditions
Ambient temperature -20 °C ... 125 °C
Degree of protection IP67, when plugged in
Specifications according to DIN EN 61984:2001
Installation height max. 2000 m
Nominal / operating voltage of power contacts 150 V
Rated surge voltage of power contacts 1.5 kV
Overvoltage category of power contacts II
Degree of pollution of power contacts 3
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.0272607xxeCl@ss 4.1272607xxeCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440102eCl@ss 8.027440102eCl@ss 9.027440103
ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002635ETIM 6.0EC002061
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC
13.239121413

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-26S1N8A6300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.