

INDUSTRIAL COMPONENT DATA

RC-06P1N124200 1593122 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-06P1N124200



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-06P1N124200
Catalog number	1593122
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-CEADB7A5B1
Generated	2026-08-06

Product Overview

Device connector, rear mounting

M23, Conect. plug. to be apar. poster wall, RC, straight, shielded: yes, Screw lock, No. of poles: 6, Direction of rotation: Standard, contact type: Male, Weld connection, Radial O-ring, 4xM2.5, Min. wall thickness: 2.7 mm, Max. wall thickness: 3.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240335
M23, Device connector rear mounting, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 6, Direction of rotation: Standard, contact connection type: Pin, Solder cup, Radial O-ring, 4x M2.5, Panel thickness min.: 2.7 mm, Panel thickness max.: 3.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Circular connectors (device side)

Thread type M23

Material specificationsFlammability rating according to UL 94 V0

Housing material Metal

Connection dataConductor connection

Connection method Solder connection

ConnectorInsulating body

Coding N

Insertion/withdrawal cycles 50

Connection method Solder cup
Contact switching type Pin
Application Signal
Number of positions 6
Direction of rotation Standard
Connection profile 6
Litz wire cross-sectionPower contactsmin. 0.08 mm²
Litz wire cross-sectionPower contactsmax. 2.5 mm²
Rated currentPower contacts 20 A
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Housing
Housing material Metal
Type of locking Screw locking mechanism
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
Environmental and real-life conditionsAmbient conditions
Degree of protection IP67
ETIM for 1593122 Connectors (EC003569)
Feature Name
Feature Value
With shield connection (EF002535)
No
With PE-connection (EF005600)
No
Housing material (EF001596)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Degree of protection (IP), mounted (EF007466)
IP67
With thread (EF003723)
Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-06P1N124200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.