

INDUSTRIAL COMPONENT DATA

RC-07S1N126100 1594593 PHOENIX CONTACT Device connector with M20 x 1.5 screw-in thread, straight, shielded: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-07S1N126100



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-07S1N126100
Catalog number	1594593
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-7BA29564B4
Generated	2026-08-06

Product Overview

Device connector with M20 x 1.5 screw-in thread, straight, shielded: yes, Screw locking, M23, No. of pos.: 7, type of contact: Socket, Solder connection, Axial O-ring, Central fixing, Panel thickness min.: 0.8 mm, Panel thickness max.: 6.5 mm

M23, Conect. plug. to be apar. poster wall, RC, straight, shielded: yes, Screw lock, No. of poles: 7, Direction of rotation: Standard, contact type: Female, Weld connection, Axial O-ring, Central fixing, Min. wall thickness: 0.8 mm, Max. wall thickness: 6.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240576 M23, Device connector front mounting, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 7, Direction of rotation: Standard, contact connection type: Socket, Solder cup, Axial O-ring, Central fixing, Panel thickness min.: 0.8 mm, Panel thickness max.: 6.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Circular connectors (device side)

ConnectorInsulating body

Coding N

Insertion/withdrawal cycles 50

Connection method Solder cup

Contact switching type Socket

Application Signal
Number of positions 7
Direction of rotation Standard
Connection profile 7
Contact diameterPower contacts 2 mm
Litz wire cross-sectionPower contactsmin. 0.08 mm²
Litz wire cross-sectionPower contactsmax. 2.5 mm²
Rated currentPower contacts 20 A
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Housing
Order information: Order contact inserts separately
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking Screw locking mechanism
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
ETIM for 1594593 Connectors (EC002635)
Feature Name
Feature Value
Number of data contacts (EF012232)
0
Number of power contacts (EF012216)
0
Type of locking (EF000208)
Other
With protective conductor (EF007468)
No
Screened (EF000881)
No
With status indication (EF001602)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-07S1N126100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.