

## INDUSTRIAL COMPONENT DATA

# RC-07S1N12WT00 1594715 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-07S1N12WT00



|                 |                   |
|-----------------|-------------------|
| Manufacturer    | PHOENIX CONTACT   |
| MPN / Reference | RC-07S1N12WT00    |
| Catalog number  | 1594715           |
| Category        | Modular connector |
| Minimum order   | 40 Pcs            |
| Document ID     | EO-CC0CC6AE5E     |
| Generated       | 2026-08-04        |

## Product Overview

Device connector, front mounting

Plug-in connector for front wall appliances, RC, straight, shielded: yes, Screw lock, M23, No. of poles: 7, contact type: Female, Soldered connection, Axial O-ring, 4x Ø 3.2

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |
|--------------|-------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1594715

Packing unit 1

GTIN 4046356202947

Custom tariff number 85366990

Data of the insulating body

Coding N

Insertion/withdrawal cycles mechanical 50

Contact connection method Solder connection

Type of contacts Socket

Application Signal

Number of positions 7

Contact diameter of power contacts 2 mm

Litz wire cross section of power contacts min. 0.08 mm<sup>2</sup>

Litz wire cross section of power contacts max. 2.5 mm<sup>2</sup>

Nominal current per power contact at 25°C 20 A

Nominal voltage, power contact 300 V

Rated surge voltage 2.5 kV

Overvoltage category II

Degree of pollution 3

Overvoltage category II

Degree of pollution 3

Housing data

Housing material GD-Zn

Type of locking Screw locking

Degree of protection (when plugged in) IP67

Thread type M23

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027279200eCl@ss  
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC001121ETIM 6.0EC001121

UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC  
13.239121413

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-07S1N12WT00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.