

INDUSTRIAL COMPONENT DATA

RC-09S2N120000 1596535 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-09S2N120000



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-09S2N120000
Catalog number	1596535
Category	Contact insert for circular connectors
Minimum order	10 Pcs
Document ID	EO-48318DF54E
Generated	2026-08-06

Product Overview

Contact insert

Contact insert, number of poles: 8+1, contact type: Female, Solder connection

Contact insert, M23, Number of poles: 8+1, Contact type: Socket, Solder cup, Series: NC, RC, RM, TU, UC, Alternative product according to RoHS II without exception 6c (Pb < 0.1 %) Item no.: 1240713

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1596535

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4046356211703

Weight per Piece (excluding packing) 7.260 g

Custom tariff number 85389099

Country of origin DE (Germany)

General

Insertion/withdrawal cycles mechanical 50

Direction of rotation of contact chamber numbering Counter direction

Coding N

Contact connection method Solder connection
Type of contacts Socket
Number of positions 9
Contact diameter of power contacts 2 mm
Litz wire cross section of power contacts min. 0.08 mm²
Litz wire cross section of power contacts max. 2.5 mm²
Nominal current per power contact at 25°C 20 A
Contact diameter of signal contacts 1 mm
Litz wire cross section of signal contacts min. 0.08 mm²
Litz wire cross section of signal contacts max. 1 mm²
Nominal current per signal contact at 25°C 8 A
Material
Insulator material PBT
Contact material CuZn
Contact surface Nickel-plated, gold coating
Specifications according to DIN EN 61984:2001
Nominal / operating voltage of power contacts 300 V
Rated surge voltage of power contacts 2.5 kV
Overvoltage category of power contacts II
Degree of pollution of power contacts 3
Nominal / operating voltage of signal contacts 300 V
Overvoltage category of signal contacts II
Degree of pollution of signal contacts 3
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Categ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-09S2N120000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.