

INDUSTRIAL COMPONENT DATA

RC-12P1N8AH000 1597587 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-12P1N8AH000



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-12P1N8AH000
Catalog number	1597587
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-FB2455FC4B
Generated	2026-08-06

Product Overview

Device connector, rear mounting

M23, Conect. plug. to be apar. wall poster., RC, straight, shielded: yes, Screw lock, No. of poles: 12, Direction of rotation: Standard, contact type: Male, Crimped connection, Axial O-ring, Central fixing M25 x 1.5, Min. wall thickness: 0.8 mm, Max. wall thickness: 6.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240858

M23, Device connector rear mounting, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 12, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, Axial O-ring, Central fastening M25 x 1.5, Panel thickness min.: 0.8 mm, Panel thickness max.: 6.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Technical dataNotesOrder information: Order crimp contacts Ø 1 mm separately

Product propertiesProduct type Circular connectors (device side)

Thread type M23

Material specificationsFlammability rating according to UL 94 V0

Connection dataConductor connection

Connection method Solder connection

ConnectorInsulating body

Note Order information: Order crimp contacts Ø 1 mm separately

Coding N

Connection method Crimp connection

Contact switching type Pin

Application Signal

Number of positions 12

Direction of rotation Standard

Connection profile 12

Contact diameterPower contacts 1 mm

Rated currentPower contacts 8 A

Rated voltage 48 V AC

74 V DC

Rated surge voltage 1.5 kV

Overvoltage category III

Degree of pollution 3

Housing

Housing material Metal

Type of locking Screw locking mechanism

Pg screw connection none

Degree of protection (plugged in) IP67

Thread type M23

Environmental and real-life conditionsAmbient conditions

Degree of protection IP67

Ambient temperature (storage/transport) 15 °C ... 25 °C

Permissible humidity (storage/transport) 50 % ... 65 %

ETIM for 1597587 Connectors (EC003569)

Feature Name

Feature Value

With shield connection (EF002535)

No

With PE-connection (EF005600)

No

Inflammability class of insulation material according to UL94 (EF002521)

V0

Degree of protection (IP), mounted (EF007466)

IP67

With thread (EF003723)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-12P1N8AH000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.