

INDUSTRIAL COMPONENT DATA

RC-12P2N129091 1597968 PHOENIX CONTACT Coupler connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-12P2N129091



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-12P2N129091
Catalog number	1597968
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-E1529DF34D
Generated	2026-08-03

Product Overview

Coupler connector

M23, Plug-in coupling connector, RC, straight, shielded: yes, Screw lock, No. of poles: 12, Direction of rotation: Opposite movement, contact type: Male, Solder connection, cable diameter range: 7.5 mm ... 9.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240905

M23, Coupler connector, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 12, Direction of rotation: Counter direction, contact connection type: Pin, Solder cup, cable diameter range: 7.5 mm ... 9.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Circular connector (cable-side)

ConnectorInsulating body

Coding N

Insertion/withdrawal cycles 50

Connection method Solder cup

Contact switching type Pin

Application Signal

Number of positions 12

Direction of rotation Counter direction

Connection profile 12
Contact diameterPower contacts 1 mm
Litz wire cross-sectionPower contactsmín. 0.08 mm²
Litz wire cross-sectionPower contactsmáx. 1 mm²
Rated currentPower contacts 8 A
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Housing
Housing material Metal
Type of locking Screw locking mechanism
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
Seal
External cable diameter 7.5 mm ... 9.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-12P2N129091 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.