

**INDUSTRIAL COMPONENT DATA**

# RC-12S1N121L0Y 1598511 PHOENIX CONTACT Cable connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-12S1N121L0Y



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | RC-12S1N121L0Y                    |
| Catalog number  | 1598511                           |
| Category        | Sensor-actuator connector chassis |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-7BBB7CB809                     |
| Generated       | 2026-08-03                        |

## Product Overview

Cable connector

Industrial connector, with Pg13.5 connection thread, straight, shielded: no, Screw lock, M23, No. of poles: 12, Contact type: Female, Soldered connection, Cable diameter: 9 mm ... 13 mm

M23, Crimp contact, series: RC, straight, shielded: no, Screw lock, No. of poles: 12, Direction of rotation: Standard, contact connection type: Female, Solder cup, coding: N

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |
|--------------|-------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1598511

Packing unit 1

GTIN 4046356221009

Custom tariff number 85366990

Data of the insulating body

Coding N

Insertion/withdrawal cycles mechanical 50

Contact connection method Solder connection

Type of contacts Socket

Application Signal

Number of positions 12

Contact diameter of power contacts 1 mm

Litz wire cross section of power contacts min. 0.08 mm<sup>2</sup>

Litz wire cross section of power contacts max. 1 mm<sup>2</sup>

Nominal current per power contact at 25°C 8 A

Nominal voltage, power contact 150 V

Rated surge voltage 1.5 kV

Overvoltage category II

Degree of pollution 3

Overvoltage category II

Degree of pollution 3

Housing data

Housing material Metal

Type of locking Screw locking

Degree of protection (when plugged in) IP65

IP67

Thread type M23

Cable seal data

Cable diameter 9 mm ... 13 mm

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260701eCl@ss 6.027260708eCl@ss  
7.027440312eCl@ss 8.027440102eCl@ss 9.027440103

ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC001121ETIM 6.0EC002061

UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC  
13.239121413

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-12S1N121L0Y with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.