


**INDUSTRIAL COMPONENT DATA**

# PTFIX 12X2,5-NS15A BK 3274136 PHOENIX CONTACT

## Distribution block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 12X2,5-NS15A BK



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTFIX 12X2,5-NS15A BK       |
| Catalog number  | 3274136                     |
| Category        | Feed-through terminal block |
| Minimum order   | 8 Pcs                       |
| Document ID     | EO-D9DC96DA6C               |
| Generated       | 2026-08-05                  |

### Product Overview

Distribution block

Distribution block, Block with horizontal alignment, nominal voltage: 690 V, nominal current: 24 A, number of connections: 12, connection type: Push-in connection, cross-section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting class: NS 15, color: black

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; FIX block System

### Additional Product Information

Key Commercial Data

Orderkey 3274136

Packing unit 8 pc

Minimum order quantity 8 pc

Note Made to Order (non-returnable)

Catalog page Page 141 (C-1-2017)

GTIN 4055626393605

Weight per Piece (excluding packing) 25.000 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note Notes on operation The blocks can be bridged with one another via the conductor shaft. For corresponding plug-in bridges, see accessories

Number of levels 1  
Number of connections 12  
Potentials 1  
Nominal cross section 2.5 mm<sup>2</sup>  
Color black  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 0.77 W (the value is based on one connection block and is multiplied according to the pin assignment)  
Maximum load current 32 A  
Maximum total current 48 A  
Nominal current I<sub>N</sub> 24 A  
Nominal voltage U<sub>N</sub> 690 V  
Open side panel No  
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11  
Back of the hand protection guaranteed  
Finger protection guaranteed  
Result of surge voltage test Test passed  
Surge voltage test setpoint 9.8 kV  
Result of power-frequency withstand voltage test Test passed  
Power frequency withstand voltage setpoint 1.89 kV  
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed  
Result of bending test Test passed  
Bending test rotation speed 10 rpm  
Bending test turns 135  
Bending test....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 12X2,5-NS15A BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.