


INDUSTRIAL COMPONENT DATA

FMC 1,5/14-ST-3,5 BD:1-14 1702118 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FMC 1,5/14-ST-3,5 BD:1-14



Manufacturer	PHOENIX CONTACT
MPN / Reference	FMC 1,5/14-ST-3,5 BD:1-14
Catalog number	1702118
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-2494027F2E
Generated	2026-08-06

Product Overview

Plug

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Tin, contact type: Female connection, Number of potentials: 14, Number of rows: 1, Number of poles per row: 14, number of connections: 14, family of articles: FMC 1.5/.. -ST, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, Stecksystem: MINICOMBICON, Locking: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1702118

Packing unit 1

GTIN 4046356572309

Custom tariff number 85366990

Dimensions

Length [l] 22.9 mm

Width [w] 49.75 mm

Height [h] 7.75 mm

Pitch 3.5 mm

Dimension a 45.5 mm

General

Range of articles FMC 1,5/...-ST

Number of positions 14

Connection method Push-in spring connection

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²**Connection data**Conductor cross section solid min. 0.2 mm²Conductor cross section solid max. 1.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 1.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Minimum AWG according to UL/CUL 24

Maximum AWG according to UL/CUL 16

Specifications for ferrules

Recommended crimping pliers 1212034 CRIMPFOX 6

Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 5 mm ... 7 mmCross section: 0.34 mm²; Length: 7 mmCross section: 0.5 mm²; Length: 8 mm ... 10 mmCross section: 0.75 mm²; Length: 8 mm ... 10 mmCross section: 1 mm²; Length: 8 mm ... 10 mmCross section: 1.5 mm²; Length: 10 mm...**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / FMC 1,5/14-ST-3,5 BD:1-14 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.