

**INDUSTRIAL COMPONENT DATA**

# RC-16P1N122200 1600540 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-16P1N122200



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                              |
| MPN / Reference | RC-16P1N122200                               |
| Catalog number  | 1600540                                      |
| Category        | Circular connector, mounting (without cable) |
| Minimum order   | 1 Pcs                                        |
| Document ID     | EO-71D17FB9F0                                |
| Generated       | 2026-08-06                                   |

## Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, RC, straight, shielded: yes, Screw lock, No. of poles: 16, Direction of rotation: Standard, contact type: Male, Weld connection, Flat joint, 4x Ø2.7, flange measurement: 25 mm x 25 mm, Min. wall thickness: 1 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb&lt; 0.1%) item code: 1241222

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |
|--------------|-------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1600540

Packing unit 40 pc

Note Made to Order (non-returnable)

GTIN 4046356230582

Weight per Piece (excluding packing) 34.440 g

Custom tariff number 85366990

Country of origin DE (Germany)

Data of the insulating body

Coding N

Insertion/withdrawal cycles mechanical 50

Contact connection method Solder connection

Type of contacts Pin  
Application Signal  
Number of positions 16  
Contact diameter of power contacts 1 mm  
Litz wire cross section of power contacts min. 0.08 mm<sup>2</sup>  
Litz wire cross section of power contacts max. 1 mm<sup>2</sup>  
Nominal current per power contact at 25°C 8 A  
Nominal voltage, power contact 150 V  
Rated surge voltage 1.5 kV  
Overvoltage category II  
Degree of pollution 3  
Overvoltage category II  
Degree of pollution 3  
Housing data  
Housing material Metal  
Flange dimensions 25 mm x 25 mm  
Type of locking Screw locking  
Degree of protection (when plugged in) IP67  
Thread type M23  
Environmental Product Compliance  
REACH SVHC Lead 7439-92-1  
China RoHS Environmentally Friendly Use Period = 50  
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"  
Classifications  
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027279200eCl@ss  
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102  
ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC001121ETIM 6.0EC001121  
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC  
13.239121413  
ETIM for 1600540 Connectors (EC002635)  
Feature Name....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-16P1N122200 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.