

INDUSTRIAL COMPONENT DATA

RC-16S1N12T0EM 1601016 PHOENIX CONTACT Cable connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-16S1N12T0EM



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-16S1N12T0EM
Catalog number	1601016
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-DF4830F318
Generated	2026-08-04

Product Overview

Cable connector

Plug-in connector for cables, RC, angled, shielded: yes, Screw lock, M23, No. of poles: 16, contact type: Female, Soldered connection, cable diameter range: 3 mm ... 10.5 mm

M23, Cable connector, series: RC, angled, shielded: yes, Screw locking mechanism, No. of pos.: 16, Direction of rotation: Standard, contact connection type: Socket, Solder cup, cable diameter range: 3 mm ... 10.5 mm, coding: N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Circular connector (cable-side)

ConnectorInsulating body

Coding N

Insertion/withdrawal cycles 50

Connection method Solder cup

Contact switching type Socket

Application Signal

Number of positions 16

Direction of rotation Standard

Connection profile 16

Contact diameterPower contacts 1 mm

Litz wire cross-sectionPower contactsmin. 0.08 mm²

Litz wire cross-sectionPower contactsmax. 1 mm²

Rated currentPower contacts 8 A

Rated voltage 48 V AC

74 V DC

Rated surge voltage 1.5 kV

Overvoltage category III

Degree of pollution 3

Housing

Housing material Metal

Type of locking Screw locking mechanism

Pg screw connection none

Degree of protection (plugged in) IP67

Thread type M23

Seal

External cable diameter 3 mm ... 10.5 mm

Seal material NBR

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-16S1N12T0EM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.