

INDUSTRIAL COMPONENT DATA

RC-16S1N8AC3FA 1614508 PHOENIX CONTACT Rear panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-16S1N8AC3FA



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-16S1N8AC3FA
Catalog number	1614508
Category	Modular connector
Minimum order	20 Pcs
Document ID	EO-B323E66D88
Generated	2026-08-06

Product Overview

Rear panel feed-through

M23, Rear wall feedthrough, RC, straight, shielded: yes, Screw lock, No. of poles: 16, Direction of rotation: Standard, type of contact: Female, Crimped connection, Radial O-ring, 4xM3, Max. wall thickness: 2.5 mm, cable diameter range: 9.5 mm ... 10.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1241360

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1614508

Packing unit 1

GTIN 4046356434287

Custom tariff number 85366990

Data of the insulating body

Note Order information: Order crimp contacts Ø 1 mm separately

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Application Signal

Number of positions 16

Contact diameter of power contacts 1 mm

Nominal current per power contact at 25°C 8 A

Nominal voltage, power contact 150 V

Rated surge voltage 1.5 kV

Overvoltage category II

Degree of pollution 3

Overvoltage category II

Degree of pollution 3

Housing data

Note Order information: Order contact inserts and cable clamping/shield accessories separately

Housing material Metal

Type of locking Screw locking

Degree of protection (when plugged in) IP67

Thread type M23

Cable seal data

Cable diameter 9.5 mm ... 10.5 mm

Sealing material NBR

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC001121ETIM 6.0EC001121

UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC
13.239121413

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-16S1N8AC3FA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.