

INDUSTRIAL COMPONENT DATA

RC-17P1N8AC1X7 1601566 PHOENIX CONTACT Rear panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-17P1N8AC1X7



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-17P1N8AC1X7
Catalog number	1601566
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-4AC3BA21AC
Generated	2026-08-06

Product Overview

Rear panel feed-through

M23, Rear wall pass-through, RC, straight, shielded: yes, Screw lock, No. of poles: 17, Direction of rotation: Standard, type of contact: Male, Crimped connection, Flat joint, 4xM3, Max. wall thickness: 2.5 mm, cable diameter range: 4.5 mm ... 5.5 mm, encoding:N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1601566

Packing unit 1

GTIN 4046356235426

Custom tariff number 85366990

Data of the insulating body

Note Order information: Order crimp contacts Ø 1 mm separately

Coding N

Contact connection method Crimp connection

Type of contacts Pin

Application Signal

Number of positions 17

Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Nominal voltage, power contact 150 V
Rated surge voltage 1.5 kV
Overvoltage category II
Degree of pollution 3
Overvoltage category II
Degree of pollution 3
Housing data
Note Order information: Order contact inserts and cable clamping/shield accessories separately
Housing material Metal
Type of locking Screw locking
Degree of protection (when plugged in) IP67
Thread type M23
Cable seal data
Cable diameter 4.5 mm ... 5.5 mm
Litz wire bundle diameter 4.6 mm
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC001121ETIM 6.0EC001121
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC
13.239121413
ETIM for 1601566 Connectors (EC002635)
Feature Name
Feature Value
Number of data contacts (EF012232)
0
Number of....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-17P1N8AC1X7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.