

INDUSTRIAL COMPONENT DATA

MSTBW 2,5/ 2-G-5,08 GY 1707553 PHOENIX CONTACT Base housing, rated current: 12 A, number of poles: 2, pitch:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBW 2,5/ 2-G-5,08 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBW 2,5/ 2-G-5,08 GY
Catalog number	1707553
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-B3BD35DFF2
Generated	2026-08-06

Product Overview

Base housing, rated current: 12 A, number of poles: 2, pitch: 5.08 mm, color: gray, contact surface: Tin, mounting: Wave solder

Printed circuit board base housing, nominal section: 2.5 mm², color: gray, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MSTBW 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential:1, plug-in system: CLASSIC COMBICON, Plug-in face orientation: Standard, Locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Header, nominal current: 12 A, number of positions: 2, pitch: 5.08 mm, color: gray, contact surface: Tin, mounting: Wave soldering

Your advantages

Maximum flexibility when it comes to device design - one header for connectors with different connection technologiesWell-known mounting principle allows worldwide useStand-offs enable the PCB to be cleaned or sealedKey

Commercial Data

Orderkey 1707553

Packing unit 1

GTIN 4046356930901

Custom tariff number 85366930

General

Range of articles MSTBW 2,5/..-G

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Color gray

Number of positions 2

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

eCl@ss

eCl@ss 5.1 27260701

eCl@ss 6.0 27260704

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

UNSPSC

UNSPSC 13.2 39121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBW 2,5/ 2-G-5,08 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.