

**INDUSTRIAL COMPONENT DATA**

# RC-17S1N8A4300 1602110 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-17S1N8A4300



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                              |
| MPN / Reference | RC-17S1N8A4300                               |
| Catalog number  | 1602110                                      |
| Category        | Circular connector, mounting (without cable) |
| Minimum order   | 1 Pcs                                        |
| Document ID     | EO-26A8B30C0E                                |
| Generated       | 2026-08-06                                   |

## Product Overview

Device connector, rear mounting

M23, Conect. plug. to be apar. poster wall, RC, straight, Screw lock, No. of poles: 17, Rotation direction: Standard, contact type: Female, Crimped connection, Radial O-ring, 4xM3, Min. wall thickness: 2.7 mm, Max. wall thickness: 3.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb&lt; 0.1%) item code: 1241483

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |
|--------------|-------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1602110

Packing unit 1

GTIN 4046356238175

Custom tariff number 85366990

Data of the insulating body

Note Order information: Order crimp contacts Ø 1 mm separately

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Application Signal

Number of positions 17

Contact diameter of power contacts 1 mm  
Nominal current per power contact at 25°C 8 A  
Nominal voltage, power contact 150 V  
Rated surge voltage 1.5 kV  
Overvoltage category II  
Degree of pollution 3  
Overvoltage category II  
Degree of pollution 3  
Housing data  
Housing material Metal  
Type of locking Screw locking  
Degree of protection (when plugged in) IP67  
Thread type M23  
Environmental Product Compliance  
REACH SVHC Lead 7439-92-1  
China RoHS Environmentally Friendly Use Period = 50  
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"  
Classifications  
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027279200eCl@ss  
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102  
ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC001121ETIM 6.0EC001121  
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC  
13.239121413  
ETIM for 1602110 Connectors (EC003569)  
Feature Name  
Feature Value  
With shield connection (EF002535)  
No  
With PE-connection (EF005600)  
No  
Inflammability class of insulation material according to UL94 (EF002521)  
V0  
Degree of protection (IP), mounted (EF007466)  
IP67  
With thread (EF003723)  
Y...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-17S1N8A4300 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.