

INDUSTRIAL COMPONENT DATA**RC-19P1NT20000 1602717 PHOENIX CONTACT Contact insert**

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-19P1NT20000



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-19P1NT20000
Catalog number	1602717
Category	Contact insert for circular connectors
Minimum order	10 Pcs
Document ID	EO-6786A333C1
Generated	2026-08-06

Product Overview

Contact insert

Contact insert, number of poles: 16+3, contact type: Male, Solder connection

Contact insert, M23, number of positions: 16+3, contact connection type: Pin, Solder-in connection, series: NC, RC, RM, TU, UC

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **PHOENIX CONTACT > Field Device Connectors (FDC)****Additional Product Information**

Technical dataProduct propertiesSeries NC

RC

RM

TU

UC

Application Signal

Number of positions 19

Connection profile 16+3

Coding N

Thread type M23

Electrical propertiesContact

Contact diameter 1.5 mm

Max. current 10 A

Nominal voltage UN 48 V AC 74 V DC

Overvoltage category III

Degree of pollution 3

Rated surge voltage 1.5 kV

Contact

Contact diameter 1 mm

Max. current 8 A

Connection dataConnection method Solder-in connection

ConnectorDirection of rotation Standard

ETIM for 1602717 Connectors (EC003557)

Feature Name

Feature Value

Number of poles (EF001391)

19

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-19P1NT20000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.