

INDUSTRIAL COMPONENT DATA

RCK-TGUM/BL12/20,0PUR-U 1514469 PHOENIX CONTACT

Connector component

Brand: PHOENIX CONTACT | Manufacturer Part Number: RCK-TGUM/BL12/20,0PUR-U



Manufacturer	PHOENIX CONTACT
MPN / Reference	RCK-TGUM/BL12/20,0PUR-U
Catalog number	1514469
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-19BD415D8E
Generated	2026-08-06

Product Overview

Connector component

M23 connection socket, straight, 12 poles, with 20 m main cable

Master cable, number of positions: 12, status display: No; master cable connection: M23 socket, cable length: 20 m, shielding: no, Alternative product in accordance with RoHS II without Exemption 6c (Pb)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Master cable, assembled

Number of positions 12

Data management status

Article revision 09

Electrical propertiesNominal voltage UN 48 V AC

60 V DC

Connection dataConnection method Fixed connection

SignalingStatus display present No

Material specificationsMaterial Housing PUR

Material of contact, master cable side CU alloy

Material of the contact carrier on the master cable side PA

Material of contact surface, master cable side gold-plated

Cable/line Cable length 20 m
PUR/PVC black [PUR]
Dimensional drawing
Cable weight 107.4 kg/km
UL AWM Style 20549 (80°C/300 V)
Number of positions 11
Shielded no
Cable type PUR/PVC black [PUR]
Conductor structure signal line 19x 0.15 mm
AWG signal line 22
Conductor cross section 8x 0.34 mm² (Signal line)
3x 0.75 mm² (power line)
Wire diameter incl. insulation 1.3 mm ±0.1 mm (Signal line)
1.8 mm ±0.1 mm (power line)
External cable diameter 8.50 mm ±0.2 mm
Outer sheath, material PUR
External sheath, color black RAL 9005
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, blue, green/yellow, white, green, yellow, gray, pink, red, black, violet
Inner sheath thickness ≥ 0.15 mm
Thickness, outer sheath ≥ 0.38 mm
Overall twist Wires twisted in layers
Max. conductor resistance ≤ 53 ?/km (Signal line)
≤ 26 ?/km (power line)
Insulation resistance ≥ 5 M?·km
Nominal voltage, cable 300 V AC
Test voltage Core/Core 2000 V (50 Hz, 5 min.)
Minimum bending radius, fixed instal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RCK-TGUM/BL12/20,0PUR-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.