

INDUSTRIAL COMPONENT DATA

REL-FO/L-230AC/1X21 1308317 PHOENIX CONTACT Plug-in miniature relay, FASTON connection, 1 switch, status ind..

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-FO/L-230AC/1X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-FO/L-230AC/1X21
Catalog number	1308317
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-512272A822
Generated	2026-08-04

Product Overview

Plug-in miniature relay, FASTON connection, 1 switch, status indication: LED (yellow), Input voltage: 230 V AC

Plug-in miniature relay, FASTON connection, 1 changeover contact, status display: Yellow LED, Input voltage: 230 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Technical dataNotesGeneral Do not use to separate SELV/PELV circuits from other circuits, because safe isolation is not guaranteed. (applies to the optocoupler variants)

General The system installer must ensure the touch protection of the product (at voltages > 25 V AC/60 V DC). The product is a built-in device without protection against direct contact.

Product propertiesProduct type Single relay

Product family ESSENTIAL edition

Operating mode 100% operating factor

Mechanical service life approx. 3x 10⁷cycles

Relay type Electromechanical relay

Insulation characteristics: Air clearances and creepage distances between the power circuits

Insulation Basic insulation

Overvoltage category II

Pollution degree 3

Electrical propertiesMaximum power dissipation for nominal condition 0.9 W

Test voltage (Winding/contact) 5 kVrms(50 Hz, 1 min., winding/contact)

Test voltage () 1 kVrms(50 Hz, 1 min., open contact)

Air clearances and creepage distances between the power circuits

Rated insulation voltage 250 V AC

Rated surge voltage 2.5 kV

Input dataCoil side

Nominal input voltage UN 230 V AC

Input voltage range 184 V AC ... 253 V AC

Mains frequency 50/60 Hz

Drive and function monostable

Drive (polarity) non-polarized

Typical input current at UN 4.5 mA (50 Hz)

Input power dissipation for UN 1 W

Typical response time 2 ms ... 15 ms

Typical release time range 5 ms ... 20 ms

Status display Yellow LED

Coil resistance 24100 ? ± 10 %

Output dataSwitching

Contact switching type 1 changeover contact....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-FO/L-230AC/1X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.