

INDUSTRIAL COMPONENT DATA

REL-PR3-220DC/3X21 2909055 PHOENIX CONTACT Plug-in high-power relay with power contacts, 3 changeover contac..

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-PR3-220DC/3X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-PR3-220DC/3X21
Catalog number	2909055
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-AA19B97ADE
Generated	2026-08-04

Product Overview

Plug-in high-power relay with power contacts, 3 changeover contacts, coil voltage: 220 V DC

Pluggable high-power relays with power contacts, 3 switches, coil voltage: 220 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2909055

Packing unit 1

Catalog page Page 312 (C-5-2019)

GTIN 4055626358789

Custom tariff number 85364900

Drawings

Dimensions

Coil side

General

Standards and Regulations

Classifications

Note

Ambient conditions

Contact side

Connection data

Environmental Product Compliance

Drawings

Diagram

Operating voltage range

Diagram

Interrupting rating

Diagram

Electrical service life

Diagram

Service life reduction factor

Circuit diagram

[Back to top](#)Note

Note The outputs are not suitable for switching different outer conductors.

Do not use to separate SELV / PELV circuits from other circuits, because safe isolation is not guaranteed.

[Back to top](#)Dimensions

Width 38.6 mm

Height 36.1 mm

Depth 45.5 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Maximum altitude ≤ 2000 m

Degree of protection RT I

≥ IP54 (Installation location)

[Back to top](#)Coil side

Nominal input voltage UN 220 V DC

Typical input current at UN 6 mA

Non-operate voltage < 132 V DC

Safe operate voltage > 176 V DC

Typical response time 20 ms

Typical release time 15 ms

Coil resistance 37000 Ω ±10 %

Power dissipation for nominal condition 1.34 W

[Back to top](#)Contact side

Contact type 3 PDTs

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 440 V AC

250 V DC

Minimum switching voltage 10 V (At 24 mA)

Min. switching current 10 mA (at 24 V)

Maximum inrush current 50 A (20 ms, N/O contacts)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-PR3-220DC/3X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.