


INDUSTRIAL COMPONENT DATA

REL-SR- 24DC/2X21/FG 2908777 PHOENIX CONTACT Safety relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-SR-24DC/2X21/FG



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-SR-24DC/2X21/FG
Catalog number	2908777
Category	Switching relay
Minimum order	20 Pcs
Document ID	EO-4855BC1B16
Generated	2026-08-05

Product Overview

Safety relays

Safety relay with forced conduction contacts according to DIN EN 61810-3, contact type 2 switches. The requirements for type A according to DIN EN 61810-3 are met if the connection is made as 1 normally open contact/1 normally closed contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data

Orderkey 2908777

Packing unit 20 pc

Minimum order quantity 20 pc

Catalog page Page 457 (C-5-2017)

GTIN 4055626338651

Weight per Piece (excluding packing) 19.450 g

Custom tariff number 85364190

Country of origin CZ (Czech Republic)

Dimensions

Width 12.6 mm

Height 29 mm

Depth 25.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 70 °C

Ambient temperature (storage/transport) -25 °C ... 70 °C

Coil side

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN see diagram

Typical input current at UN 29 mA

Typical response time 10 ms

Typical release time 4 ms

Power dissipation for nominal condition 0.7 W

Contact side

Contact type 2 PDT

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC

Minimum switching voltage 15 V

Min. switching current 10 mA

Maximum inrush current 6 A

Limiting continuous current 6 A

Interrupting rating (ohmic load) max. 144 W (at 24 V DC)

288 W (at 48 V DC)

88 W (at 110 V DC)

110 W (at 220 V DC)

1500 VA (for 250 V AC)

Switching capacity min. 0.24 W

Switching capacity 2 A (at 24 V, DC13)

3 A (at 230 V, AC15)

Motor load according to UL 508 10 LRA / 0,5 FLA

General

Operating mode 100% operating factor

Degree of protection IP20

Mechanical service life approx. 107cycles

B10d 600000 Cycles (AC1; 250 V / 6 A; 1 NO)

900000 Cycles (AC1; 250 V / 3 A; 1 NO)

1800000 Cycles (AC1; 250 V / 1,5 A; 1 NO)

180000 Cycles (AC15; 250 V / 3 A; 1 NO)

560000 Cycles (AC15; 250 V / 2 A; 1 NO)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-SR-24DC/2X21/FG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.