

INDUSTRIAL COMPONENT DATA

EMG 10-REL/KSR-230/21-LC AU 2964393 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMG 10-REL/KSR-230/21-LC AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMG 10-REL/KSR-230/21-LC AU
Catalog number	2964393
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-8DF74D52D2
Generated	2026-08-04

Product Overview

Relay Module

Relay module, with soldered mini-switching relay, gold contact for small powers, 1 switched contact, input voltage 230 V AC/DC

Relay module, with soldered relay, gold-plated contact for small powers, 1 changeover contact, input voltage 230 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2964393

Packing unit 10 pc

Catalog page Page 134 (IF-2011)

GTIN 4017918107451

Weight per Piece (excluding packing) 43.000 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 10.6 mm

Height 75 mm
Depth 62.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 40 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Coil side
Nominal input voltage UN 230 V AC/DC
Input voltage range in reference to UN 0.8 ... 1.1
Typical input current at UN 5 mA
Typical response time 7 ms
Typical release time 11 ms
Protective circuit Bridge rectifier Bridge rectifier
Surge protection Varistor
Operating voltage display Yellow LED
Power dissipation for nominal condition 1.15 W
Contact side
Contact type Double contact, 1 PDT
Type of switch contact Double contact
Contact material AgPd60, hard gold-plated
Maximum switching voltage 30 V AC
36 V DC
Maximum inrush current 0.2 A
Limiting continuous current 0.5 A
Interrupting rating (ohmic load) max. 5 W (at 24 V DC)
Contact side (with destroyed gold layer)
Note the following values are applicable if a gold layer is destroyed
Maximum switching voltage 125 V AC
150 V DC
Limiting continuous current 2 A
Maximum inrush current 2 A
Interrupting rating (ohmic load) max. 29 W (at 24 V DC)
29 W (at 48 V DC)
29 W (at 60 V DC)
60 VA (for 250 V AC)
General
Test voltage relay winding/relay c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMG 10-REL/KSR-230/21-LC AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.