


INDUSTRIAL COMPONENT DATA

EMG 10-REL/KSR- 24/21-LC 2942658 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMG 10-REL/KSR-24/21-LC



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMG 10-REL/KSR-24/21-LC
Catalog number	2942658
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-9E24D68610
Generated	2026-08-03

Product Overview

Relay Module

Relay module, with soldered mini-switching relay, contact (AgNi): Medium to high powers, 1 switched contact, input voltage 24 V AC/DC

Relay module, with soldered-in miniature switching relay, contact (AgNi): Medium to large loads, 1 PDT, input voltage 24 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Technical dataNotesUtilization restriction

EMC note EMC: class A product, see manufacturer's declaration in the download area

Product propertiesProduct type Relay Module

Product family EMG

Application Universal

Operating mode 100% operating factor

Mechanical service life approx. 2x 10⁷cycles

Data management status

Date of last data management 02.05.2024

Article revision 09

Insulation characteristics

Insulation Basic insulation
Overvoltage category III
Pollution degree 2
Electrical properties Maximum power dissipation for nominal condition 0.5 W
Test voltage (Winding/contact) 4 kV AC (50 Hz, 1 min., winding/contact)
Input data Coil side
Nominal input voltage UN 24 V AC/DC
Input voltage range 21.6 V AC/DC ... 26.4 V AC/DC (20 °C)
Drive and function monostable
Drive (polarity) polarized
Typical input current at UN 21 mA
Typical response time 7 ms
Typical release time 11 ms
Protective circuit Bridge rectifier; Bridge rectifier
Operating voltage display Yellow LED
Output data Switching
Contact switching type 1 changeover contact
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Limiting continuous current 6 A
Maximum inrush current 8 A
Interrupting rating (ohmic load) max. 140 W (at 24 V DC)
53 W (at 48 V DC)
45 W (at 60 V DC)
35 W (at 110 V DC)
55 W (at 220 V DC)
1500 VA (for 250 V AC)
Connection data Coil side
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Condu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMG 10-REL/KSR-24/21-LC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.