

INDUSTRIAL COMPONENT DATA

EMG 10-REL/KSR-G 24/ 1-LC 2942108 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMG 10-REL/KSR-G 24/ 1-LC



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMG 10-REL/KSR-G 24/ 1-LC
Catalog number	2942108
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-65FDC67BEB
Generated	2026-08-01

Product Overview

Relay Module

Relay module, with soldered mini-switching relay, contacts (AgNi): Medium to large powers, 1 open contact, input voltage 24 V DC

Relay module, with soldered relay, contacts (AgNi): medium to large powers, 1 closing contact, 24 V DC input voltage

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2942108

Packing unit 10 pc

Catalog page Page 133 (IF-2011)

GTIN 4017918080594

Weight per Piece (excluding packing) 36.050 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 10.6 mm

Height 75 mm
Depth 53.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 40 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Coil side
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.8 ... 1.1
Typical input current at UN 21 mA
Typical response time 7 ms
Typical release time 11 ms
Protective circuit Reverse polarity protection Polarity protection diode
Free-wheeling diode Damping diode
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.5 W
Contact side
Contact type Single contact, 1 N/O contact
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 12 V
Min. switching current 100 mA
Maximum inrush current 8 A
Limiting continuous current 6 A
Interrupting rating (ohmic load) max. 140 W (at 24 V DC)
60 W (at 48 V DC)
45 W (at 60 V DC)
35 W (at 110 V DC)
55 W (at 220 V DC)
1500 VA (for 250 V AC)
General
Test voltage relay winding/relay contact 4 kV AC (50 Hz, 1 min.)
Operating mode 100% operating factor
Degree of protection IP20
Mechanical service life approx. 2x 10⁷ cycles
Mounting position any
As...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMG 10-REL/KSR-G 24/ 1-LC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.