

INDUSTRIAL COMPONENT DATA

EMG 22-REL/KSR- 24/21 2951885 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMG 22-REL/KSR-24/21



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMG 22-REL/KSR-24/21
Catalog number	2951885
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-92C29AF399
Generated	2026-08-01

Product Overview

Relay Module

Relay module, with soldered mini-switching relay, contact (AgNi): Medium to high powers, 1 switched contact, input voltage 24 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 2951885

Packing unit 10 pc

Catalog page Page 135 (IF-2011)

GTIN 4017918084295

Weight per Piece (excluding packing) 63.930 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 22.5 mm

Height 75 mm

Depth 62.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Coil side
Nominal input voltage UN 24 V AC/DC
Input voltage range in reference to UN 0.9 ... 1.1
Typical input current at UN 18 mA
Typical response time 8 ms
Typical release time 10 ms
Protective circuit Bridge rectifier Bridge rectifier
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.43 W
Contact side
Contact type Single contact, 1-PDT
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Maximum inrush current 8 A
Limiting continuous current 6 A
Interrupting rating (ohmic load) max. 144 W (at 24 V DC)
58 W (at 48 V DC)
48 W (at 60 V DC)
50 W (at 110 V DC)
80 W (at 220 V DC)
1500 VA (for 250 V AC)
General
Test voltage relay winding/relay contact 5 kVrms(50 Hz, 1 min.)
Operating mode 100% operating factor
Degree of protection IP20
Mechanical service life approx. 5x 10⁷cycles
Mounting position any
Assembly instructions In rows with zero spacing
Connection data input side
Connection name Coil side
Connection method Scr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMG 22-REL/KSR-24/21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.