

INDUSTRIAL COMPONENT DATA

F-MS-T1/T2 50 ST 2800191 PHOENIX CONTACT Type 1/2 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: F-MS-T1/T2 50 ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	F-MS-T1/T2 50 ST
Catalog number	2800191
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	10 Pcs
Document ID	EO-69EF29591B
Generated	2026-08-03

Product Overview

Type 1/2 surge protection plug

N-PE replacement connector for VAL-MS-T1/T2 335/12.5 lightning and surge current discharger.

N-PE replacement plug for VAL-MS-T1/T2 335/12.5 plug-in lightning/surge arrester.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Replacement plug

Product family VALVETRAB MS

IEC test classification I / II

T1 / T2

T1

EN type T1 / T2

T1

IEC power supply system TN-S

TT

Type DIN rail module, two-section, divisible

Number of positions 1

Surge protection fault message optical

Data management status

Article revision 05

Insulation characteristics

Overvoltage category III

Pollution degree 2

Electrical propertiesNominal frequency fN 50 Hz (60 Hz)

Connection dataConnection method pluggable

DimensionsDimensional drawing

Width 17.7 mm

Height 47 mm

Depth 67.3 mm

Horizontal pitch 1 Div.

Material specificationsColor black (RAL 9005)

Flammability rating according to UL 94 V-0

CTI value of material 600

Insulating material PA 6.6/PBT

Material group I

Housing material PA 6.6

PBT

Protective circuitMode of protection N-PE

Direction of action N-PE

Nominal voltage UN 240/415 V AC (TN-S)

240/415 V AC (TT)

Nominal frequency fN 50 Hz (60 Hz)

Maximum continuous voltage UC 264 V AC

Residual current IPE $\leq 5 \mu\text{A}$

Standby power consumption PC $\leq 1.3 \text{ mVA}$

Nominal discharge current $I_n(8/20) \mu\text{s}$ 50 kA

Maximum discharge current $I_{\text{max}}(8/20) \mu\text{s}$ 50 kA

Impulse discharge current (10/350) μs , charge 25 As

Impulse discharge current (10/350) μs , specific energy 625 kJ/?

Impulse discharge current (10/350) μs , peak value I_{imp} 50 kA

Follow current interrupt rating I_{fi} 100 A (264 V AC)

Voltage protection level $U_p \leq 1.7 \text{ kV}$

Residual voltage $U_{\text{res}} \leq 0.6 \text{ kV}$ (at I_n)

$\leq 0.5 \text{ kV}$ (at 10 kA)

$\leq 0.5 \text{ kV}$ (at 5 kA)

$\leq 0.4 \text{ kV}$ (a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / F-MS-T1/T2 50 ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.