

INDUSTRIAL COMPONENT DATA

RF-06M1N1290DU 1617482 PHOENIX CONTACT Coupler connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: RF-06M1N1290DU



Manufacturer	PHOENIX CONTACT
MPN / Reference	RF-06M1N1290DU
Catalog number	1617482
Category	Sensor-actuator connector chassis
Minimum order	20 Pcs
Document ID	EO-3BD8902833
Generated	2026-08-05

Product Overview

Coupler connector

Plug-in coupling connector, straight, Screw lock, M23, number of poles: 6, contact type: Pin, shielded: yes, cable diameter range: 5 mm ... 13.2 mm, number of poles: 6, connection type: Solder connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1617482

Packing unit 20 pc

Note Made to Order (non-returnable)

GTIN 4046356601726

Weight per Piece (excluding packing) 98.620 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Type of locking Screw locking

Insertion/withdrawal cycles mechanical 50

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Solder connection

Type of contacts Pin

Number of positions 6

Contact diameter of power contacts 2 mm

Litz wire cross section of power contacts min. 0.08 mm²

Litz wire cross section of power contacts max. 2.5 mm²

Nominal current per power contact at 25°C 20 A

Conductor entry 5 mm ... 13.2 mm

Pg housing screw connection none

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Specifications according to DIN EN 61984:2001

Installation height max. 2000 m

Nominal / operating voltage of power contacts 50 V

Rated surge voltage of power contacts 2.5 kV

Overvoltage category of power contacts III

Degree of pollution of power contacts 3

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440102eCl@ss 8.027440102eCl@ss 9.027440103

ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC002635ETIM 6.0EC002061

UNSP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RF-06M1N1290DU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.