

INDUSTRIAL COMPONENT DATA

RF-12S1N8A9003 1607277 PHOENIX CONTACT Coupler connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: RF-12S1N8A9003



Manufacturer	PHOENIX CONTACT
MPN / Reference	RF-12S1N8A9003
Catalog number	1607277
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-E3B31BFAD7
Generated	2026-08-06

Product Overview

Coupler connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1607277

Packing unit 20 pc

Note Made to Order (non-returnable)

GTIN 4046356268462

Weight per Piece (excluding packing) 91.600 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts Ø 1 mm separately

Type of locking Screw locking

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Number of positions 12
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Conductor entry 9 mm ... 13.2 mm
Pg housing screw connection none
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material PA 6.6
Gasket and O-ring material FPM
Specifications according to DIN EN 61984:2001
Installation height max. 2000 mm
Nominal / operating voltage of power contacts 150 V
Rated surge voltage of power contacts 2.5 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Overvoltage category of signal contacts III
Degree of pollution of signal contacts 3
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RF-12S1N8A9003 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.