

INDUSTRIAL COMPONENT DATA

RF-16S1N8AA200 1613784 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RF-16S1N8AA200



Manufacturer	PHOENIX CONTACT
MPN / Reference	RF-16S1N8AA200
Catalog number	1613784
Category	Circular connector, mounting (without cable)
Minimum order	10 Pcs
Document ID	EO-D719F994DC
Generated	2026-08-02

Product Overview

Device connector, front mounting

Conect. plug. to be apar. front wall, angled, fixed, Screw lock, M23, number of poles: 16, contact type: Female, Axial O-ring, 4x Ø 3.2, shielded: yes, flange size: 26mm x 26mm, protection index: IP67, number of poles: 16, connection type: Crimped connection, series: RF

Front wall headers, rigid angle, Screw lock, M23, number of poles: 16, contact type: Female connector, axial O-ring, 4x Ø 3.2, shielded: yes, flange dimension: 26 mm x 26 mm, number of poles: 16, connection type: Crimp connection, series: RF, Replacement product according to RoHS II without exception 6c (Pb < 0.1 %) reference: 1242820

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1613784

Packing unit 10 pc

Note Made to Order (non-returnable)

GTIN 4046356402286

Weight per Piece (excluding packing) 157.900 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts Ø 1 mm separately

Type of locking Screw locking

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Number of positions 16

Contact diameter of power contacts 1 mm

Nominal current per power contact at 25°C 8 A

Pg housing screw connection none

Mounting type 4x Ø 3.2

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Material

Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)

Insulator material PA 6.6

Gasket and O-ring material FPM

Specifications according to DIN EN 61984:2001

Installation height max. 2000 m

Nominal / operating voltage of power contacts 100 V

Rated surge voltage of power contacts 1.5 kV

Overvoltage category of power contacts III

Degree of pollution of power contacts 3

Overvoltage category of signal contacts III

Degree of pollution of signal contacts 3

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127260700e...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RF-16S1N8AA200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.