

INDUSTRIAL COMPONENT DATA

RF-17P1N8AWA00S 1619560 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RF-17P1N8AWA00S



Manufacturer	PHOENIX CONTACT
MPN / Reference	RF-17P1N8AWA00S
Catalog number	1619560
Category	Sensor-actuator connector chassis
Minimum order	40 Pcs
Document ID	EO-E80B38AB24
Generated	2026-08-05

Product Overview

Device connector, front mounting

Conect. plug. to be apar. front wall, straight, SPEEDCON lock, M23, number of poles: 17, contact type: Pin, Axial O-ring, 4x Ø 3.2, shielded: yes, protection index: IP67, number of poles: 17, connection type: Crimped connection, series: RF

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1619560

Packing unit 40 pc

Note Made to Order (non-returnable)

GTIN 4046356630450

Weight per Piece (excluding packing) 107.500 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts Ø 1 mm separately

Type of locking SPEEDCON locking

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Pin

Number of positions 17

Contact diameter of power contacts 1 mm

Nominal current per power contact at 25°C 8 A

Pg housing screw connection none

Mounting type 4x Ø 3.2

Ambient conditions

Ambient temperature -20 °C ... 125 °C

Degree of protection IP67

Specifications according to DIN EN 61984:2001

Installation height max. 2000 m

Nominal / operating voltage of power contacts 100 V

Rated surge voltage of power contacts 1.5 kV

Overvoltage category of power contacts III

Degree of pollution of power contacts 3

Overvoltage category of signal contacts III

Degree of pollution of signal contacts 3

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440102eCl@ss 8.027440102eCl@ss 9.027440103

ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC002635ETIM 6.0EC002061

UNSPSC 6.0143172015UNSPSC 7.090143201404U...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RF-17P1N8AWA00S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.