

INDUSTRIAL COMPONENT DATA

RIF-0-BPT-M/ 21 2907468 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-0-BPT-M/ 21



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-0-BPT-M/ 21
Catalog number	2907468
Category	Relay socket
Minimum order	50 Pcs
Document ID	EO-8A427FC274
Generated	2026-08-06

Product Overview

Relay base

RIF-0 relay socket, for miniature power relay with 1 switched contact, push-in connection, polarity: A1-, A2+, for mounting on NS 35/7.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2907468

Packing unit 10 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 296 (C-5-2017)

GTIN 4055626210230

Weight per Piece (excluding packing) 20.000 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Width 6.2 mm

Height 93 mm

Depth 78 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C (Depends on application/assembly)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Input data

Input voltage range 12 V DC ... 24 V DC

Protective circuit Damping diode

Connection data, input side

Connection name Input side

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 1.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

0.14 mm² ... 1.5 mm² (Ferrule with plastic sleeve)

Conductor cross section AWG 24 ... 16

Connection data, output side

Connection name Output side

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 1.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

0.14 mm² ... 1.5 mm² (Ferrule with plastic sleeve)

Conductor cross section AWG 24 ... 16

General

Nominal voltage UN 250 V AC/DC (Contact side)

Nominal current IN max. 8 A (Depends on application/assembly)

Protective circuit Damping diode

Color gray

Mounting position any

Standards and Regulations

Flammability rating according to UL 94 V2

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Ch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-0-BPT-M/ 21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.