

INDUSTRIAL COMPONENT DATA

RIF-1-RPT-LDP-12DC/1IC 1078802 PHOENIX CONTACT

Pre-assembled relay module with Push-in connection, consistin..

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-1-RPT-LDP-12DC/1IC



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-1-RPT-LDP-12DC/1IC
Catalog number	1078802
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-788586EE76
Generated	2026-08-05

Product Overview

Pre-assembled relay module with Push-in connection, consisting of: relay base, power contact relay, plug-in display/interference suppression module, retaining bracket. Contact type: 1 N/O contact, max. switch-on current up to 130 A peak, 80 A (20 ms), 12 V DC input voltage

Pre-assembled relay module with push-in connection, consisting of: relay socket, relay with power contact, plug-in indication/antiparasitic module and clamping flange. Contact type: 1 normally open contact, max. input current up to 130 A peak, 80 A (20 ms) input voltage 12 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1078802

Packing unit 1

Catalog page Page 334 (C-5-2019)

GTIN 4055626796321

Custom tariff number 85364110

Drawings

Dimensions

Coil side

General

Connection data 2

Environmental Product Compliance

Classifications

Note

Ambient conditions

Contact side

Connection data

Standards and Regulations

Set Items

Drawings

Diagram

Curve A

Maximum permissible continuous voltage U_{max} with limiting continuous current on the contact side (see relevant technical data)

Curve B

Minimum permissible operate voltage U_{op} after pre-excitation (see relevant technical data)

Diagram

Contact derating

Circuit diagram

Back to top

Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Type of note
Notes on operation

Note FBS 2-6... plug-in bridge for the input side (A2) and FBS-2-8... plug-in bridge for the output side (11/21)

Back to top

Dimensions

Width 16 mm

Height 96 mm

Depth 75 mm

Back to top

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Maximum altitude ≤ 2000 m

Degree of protection RT II (Relay)

IP20 (Relay base)

$\geq$ IP54 (Installation location)

Back to top

Coil side

Nominal input voltage UN 12 V DC

Input voltage range in reference to UN see diagram

Typical input current at UN 34 mA

Typical response time 8 ms

Typical release time 10 ms

Coil voltage 12 V DC

Protective circuit Free-wheeling diode Damping diode

Operating voltage display Yellow LED

Power dissipa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-1-RPT-LDP-12DC/1IC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.