

INDUSTRIAL COMPONENT DATA

RIF-2-BPT/4X21/EX 1047028 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-2-BPT/4X21/EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-2-BPT/4X21/EX
Catalog number	1047028
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-AF8A8E7696
Generated	2026-08-03

Product Overview

Relay base

RIF-2.../EX relay socket for equipping with sealed RTIII industrial relays with 4 switched contacts for use in zone 2, push-in connection, socket for input/anti-parasitic modules, for rail mounting NS 35/7.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1047028

Packing unit 10 pc

GTIN 4055626647500

Weight per Piece (excluding packing) 67.400 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Width 31 mm

Height 96 mm

Depth with retaining bracket 75 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 60 °C (Related to the assembly)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Input data

Protective circuit depending on the selected input/suppressor modules

Connection data, input side

Connection name Coil side

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 1.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

0.14 mm² ... 1.5 mm² (Ferrule with plastic sleeve)

0.14 mm² ... 1 mm² (Ferrule with plastic sleeve, two conductors on double terminal block)

Conductor cross section AWG 26 ... 16 (solid)

26 ... 16 (flexible)

Connection data, output side

Connection name Contact side

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 1.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

0.14 mm² ... 1.5 mm² (Ferrule with plastic sleeve)

0.14 mm² ... 1 mm² (Ferrule with plastic sleeve, two conductors on double terminal block)

Conductor cross section AWG 26 ... 16 (solid)

26 ... 16 (flexible)

General

Nominal voltage UN 250 V AC/DC

Nominal current IN 4x 6 A

Protective circuit depending on the selected input/suppressor modules

Color gray

Mounting posit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-2-BPT/4X21/EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.