


INDUSTRIAL COMPONENT DATA

RIF-3-BSC/3X21 2900936 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-3-BSC/3X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-3-BSC/3X21
Catalog number	2900936
Category	Relay socket
Minimum order	1 Pcs
Document ID	EO-2DD0FF8106
Generated	2026-08-05

Product Overview

Relay base

RIF-3 relay socket..., for octal relays with 3 switched contacts, screw connection, input module/anti-parasitic socket possible, for rail mounting NS 35/7.5

RIF-3... relay base, for octal relay with 3 changeover contacts, screw connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataProduct propertiesProduct type Relay socket

Product family RIFLINE complete

Data management status

Article revision 03

Electrical propertiesNominal voltage UN 250 V AC/DC

Nominal current IN max. 10.5 A (Depends on application/assembly)

Protective circuit depending on the selected input/suppressor modules

Connection dataConnection method Screw connection

Stripping length 8 mm

Conductor cross section rigid 0.5 mm² ... 4 mm²Conductor cross-section rigid (2 conductors with same cross section) 0.5 mm² ... 2.5 mm²Conductor cross section flexible 0.5 mm² ... 4 mm²

0.5 mm² ... 4 mm² (Ferrule with plastic sleeve)

Conductor cross section flexible (2 conductors with same cross section) 0.5 mm² ... 2.5 mm²

0.5 mm² ... 1.5 mm² (TWIN ferrule with plastic sleeve)

Conductor cross section AWG 20 ... 10 (solid)

20 ... 12 (flexible)

Tightening torque 0.5 Nm ... 0.6 Nm

DimensionsWidth 40 mm

Height 96 mm

Depth Retaining bracket 90 mm (with retaining bracket)

Material specificationsColor gray (RAL 7042)

Flammability rating according to UL 94 V2 (Housing)

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -40 °C ... 85 °C (Depends on application/assembly)

Ambient temperature (storage/transport) -40 °C ... 85 °C

ApprovalsCorrosive gas test

Identification ISA-S71.04. G3 Harsh Group

EN 60068-2-60

MountingMounting type DIN rail mounting

Mounting position any

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-3-BSC/3X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.