

## INDUSTRIAL COMPONENT DATA

# ME MAX 45 F-MT G 3-3 KMGY 2201169 PHOENIX CONTACT

## Components of electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 45 F-MT G 3-3 KMGY



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME MAX 45 F-MT G 3-3 KMGY        |
| Catalog number  | 2201169                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 50 Pcs                           |
| Document ID     | EO-EF4BB3386B                    |
| Generated       | 2026-08-06                       |

### Product Overview

Components of electronic housing

Rail box, Intermediate element, flat design, without ventilation slits, width: 22.6 mm, height: 85 mm, depth: 90 mm, colour: light grey (7035)

DIN rail enclosures, intermediate element, flat type, without ventilation slot, width: 22.6 mm, height: 85 mm, depth: 90 mm, colour: light grey (similar to RAL 7035)

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 2201169

Packing unit 1

GTIN 4046356736077

Custom tariff number 85389099

General

Housing type Complete housing

Housing material Polyamide

Color (RAL) light gray

Ambient conditions

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

**Dimensions**

Length 99 mm

Width 45 mm

**Standards and Regulations**

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss

7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 3.0EC001031ETIM 4.0EC000886ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.231261501

ETIM for 2201169 Low-voltage industrial controls and switchgear (EC002779)

**Feature Name****Feature Value**

Type of enclosure (EF003086)

Open

Housing connectable (EF003088)

No

Suitable for rail mounting (EF003972)

No

Wall mounting possible (EF003973)

No

With integrated PCB-mounting connection system (EF003087)

No

Material (EF002169)

Other

Surface finishing (EF006569)

Other

RAL-number (EF000116)

7035

Width (EF000008)

22.6 mm

Height (EF000040)

85 mm

Depth (EF000049)

90 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 45 F-MT G 3-3 KMGY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.