

**INDUSTRIAL COMPONENT DATA**

# C-RC 35/M12 DIN 3240108 PHOENIX CONTACT Ring cable lug

Brand: PHOENIX CONTACT | Manufacturer Part Number: C-RC 35/M12 DIN



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | C-RC 35/M12 DIN                                   |
| Catalog number  | 3240108                                           |
| Category        | Solderless copper terminals for copper conductors |
| Minimum order   | 100 Pcs                                           |
| Document ID     | EO-633B9E5AEF                                     |
| Generated       | 2026-08-03                                        |

## Product Overview

Ring cable lug

Ring cable lug, uninsulated, 35 mm², M12

Ring lug, non-insulated, 35 mm², M12

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; TOOL fox

## Additional Product Information

Key Commercial Data

Orderkey 3240108

Packing unit 100 pc

Minimum order quantity 100 pc

Catalog page Page 490 (C-3-2017)

GTIN 4046356453257

Weight per Piece (excluding packing) 11.970 g

Custom tariff number 85369010

Country of origin CN (China)

Dimensions

Length (b) 42 mm

Width (a) 22 mm

Maximum stripping length 15 mm

Length of insulation sleeve (c) 12 mm

Inner dimension of the insulating collar (d) 9 mm

Distance between the center and the insulation sleeve (e) 19 mm

Inner diameter (f) 13 mm

Material thickness (g) 1.6 mm

Ambient conditions

Ambient temperature (operation) 110 °C

General

Color silver

Stripping length 15 mm

Material Copper

Coating tin-plated

Standards and Regulations

Design according to standard DIN 46234

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027060701eCl@ss 4.127060701eCl@ss 5.027400201eCl@ss 5.127400200eCl@ss 6.027400200eCl@ss  
7.027400203eCl@ss 8.027400204eCl@ss 9.027400204

ETIM 2.0EC000005ETIM 3.0EC000005ETIM 4.0EC001052ETIM 5.0EC001052

UNSPSC 6.0130211923UNSPSC 7.090127121703UNSPSC 1127121703UNSPSC 12.0127121703UNSPSC  
13.227121707

ETIM for 3240108 Cable terminations and insulation products (EC001052)

Feature Name

Feature Value

Flange shape (EF001339)

Ring shape

Nominal cross section (EF005124)

35 mm<sup>2</sup>

Material (EF002169)

Copper

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-RC 35/M12 DIN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.