

INDUSTRIAL COMPONENT DATA

VS-PPC-C1-RJ45-MNNA-PG9-8I6 1608113 PHOENIX CONTACT RJ45 connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-C1-RJ45-MNNA-PG9-8I6



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC-C1-RJ45-MNNA-PG9-8I6
Catalog number	1608113
Category	Accessories/spare parts for industrial connectors
Minimum order	1 Pcs
Document ID	EO-F52B26DA90
Generated	2026-08-02

Product Overview

RJ45 connector

RJ45 plug-in connector, IP67, with push-pull lock (variant 14), metal housing, for 1 gigabit/s, for flexible cable AWG 24 ... 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1608113

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 286 (PC-2011)

GTIN 4046356159951

Weight per Piece (excluding packing) 68.500 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Standards/specifications IEC PAS 61076-3-117

Number of positions 8

Connection profile RJ45

Locking type Push Pull

Shielded yes
Insertion/withdrawal cycles ≥ 200
Connection method IDC
Conductor cross section 0.2 mm² (solid)
0.14 mm² ... 0.18 mm² (flexible)
Connection cross section AWG 24 (solid)
26 ... 25 (flexible)
External cable diameter 5 mm ... 8 mm
Cable outlet straight
Color silver
Degree of protection IP65/IP67
No. of cable outlets 1
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Material data
Flammability rating according to UL 94 V0
Housing material Zinc die-cast
Housing surface material Nickel-plated
Contact carrier material PC
Contact material Copper alloy
Contact surface material Gold over nickel
Material Metal
O-ring material NBR
Cable seal material TPE
Material housing intermediate seal NBR
Height 30 mm
Electrical characteristics
Number of positions 8
Nominal voltage UN 125 V
Nominal current IN 1 A
Transmission characteristics (category) CAT6
GRP transmission properties CAT6 CAT6
Rated current 1 A
Overvoltage category I
Degree of pollution 2
Rated voltage (III/3) 72 V (DC)
Standards and Regulations
Standards/regulations IEC PAS 61076-3-117
Flammability rating according t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-C1-RJ45-MNNA-PG9-8I6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.