

INDUSTRIAL COMPONENT DATA

VS-08-BU-RJ45/BU 1689064 PHOENIX CONTACT RJ45 coupling

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-08-BU-RJ45/BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-08-BU-RJ45/BU
Catalog number	1689064
Category	Fibre optic attenuator
Minimum order	5 Pcs
Document ID	EO-DEC823D976
Generated	2026-08-03

Product Overview

RJ45 coupling

RJ45 coupling, protection rating: IP20, number of poles: 8, 1 GBit/s, CAT5 (IEC11801:2002), material: Plastic, Keystone

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1689064

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 355 (C-2-2017)

GTIN 4017918876937

Weight per Piece (excluding packing) 9.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 8

Number of slots 1

Shielded yes

Insertion/withdrawal cycles >= 1000

Connection method Female

Insulation resistance 500 M?

Degree of protection IP20

Ambient conditions

Ambient temperature (operation) -20 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Material data

Flammability rating according to UL 94 V0

Housing material Fiberglass, PBT

Housing surface material metal-plated

Contact carrier material ABS

Contact material Copper alloy

Contact surface material Gold over nickel

Electrical characteristics

Number of positions 8

Transmission characteristics (category) CAT5 (IEC 11801:2002)

GRP transmission properties CAT5 (IEC 11801:2002) CAT5 (IEC 11801:2002)

Transmission speed 1 Gbps

Rated current 1.5 A

Overvoltage category II

Degree of pollution 2

Contact resistance 20 m?

Rated voltage (III/3) 72 V (DC)

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440205e...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-08-BU-RJ45/BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.