

INDUSTRIAL COMPONENT DATA

CABLE-FLK14/OE/0,14/ 250 2305282 PHOENIX CONTACT Cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: CABLE-FLK14/OE/0,14/ 250



Manufacturer	PHOENIX CONTACT
MPN / Reference	CABLE-FLK14/OE/0,14/ 250
Catalog number	2305282
Category	PLC connection cable
Minimum order	1 Pcs
Document ID	EO-33489946AD
Generated	2026-08-03

Product Overview

Cable

Ready-made round cable; connection 1: Single conductors (14-poles) (Conductors are labeled and equipped with ferrules); Connection 2: IDC/FLK Connection Female (1x 14-pole); Cable length: 2.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2305282

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 584 (C-5-2017)

GTIN 4046356038966

Weight per Piece (excluding packing) 158.900 g

Custom tariff number 85444290

Country of origin DE (Germany)

General

Nominal voltage UN < 50 V AC

60 V DC

Max. current carrying capacity per path 1 A

Max. conductor resistance 0.16 Ω /m
Length of cable 2.5 m
Single wire, cross section 0.14 mm²
Single wire, cross section [AWG] 26
Conductor construction: Number of litz wires: 7
Single wire, material Cu tin-plated
Test voltage 0.8 kV
External diameter 6.4 mm
Cable, preassembly Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding no
Environmental conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Flame resistance IEC 60332-1
DIN VDE 0482 Part 332-1
Connector 1
Connection name Field level
Connection method IDC/FLK socket strip
Number of connections 1
Number of positions 14
Pitch 2.54 mm
Connector 2
Connection name Controller level
Connection method Single wires
Number of positions 14
Note The wires are marked and fitted with ferrules.
Supported controller
Controller universal
Color code
Connector 1 = connector 2 (optional) = wire color IDC/FLK14 (1) = black
IDC/FLK14 (2) = brown
IDC/FLK14 (3) = red
IDC/FLK14 (4) = orange
IDC/FLK14 (5) = yellow
IDC/FLK14 (6) = green
IDC/FLK14 (7) = blue
IDC/FLK14 (8) = violet
IDC/FLK14 (9) = gray
IDC/FLK14 (10) = white
IDC/FLK14 (11) = wh...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CABLE-FLK14/OE/0,14/ 250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.