

INDUSTRIAL COMPONENT DATA

FLK 34/EZ-DR/ 400/KONFEK 2299521 PHOENIX CONTACT Cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLK 34/EZ-DR/ 400/KONFEK



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLK 34/EZ-DR/ 400/KONFEK
Catalog number	2299521
Category	PLC connection cable
Minimum order	1 Pcs
Document ID	EO-A0E444D256
Generated	2026-08-01

Product Overview

Cable

Ready-made round cable; Connection 1: Female IDC/FLK connection (1x 34-poles); Connection 2: Female IDC/FLK connection (1x 34-poles); Cable length: 4 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2299521

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 589 (C-5-2017)

GTIN 4017918886240

Weight per Piece (excluding packing) 451.600 g

Custom tariff number 85444290

Country of origin DE (Germany)

General

Nominal voltage UN < 50 V AC

60 V DC

Max. current carrying capacity per path 1 A

Max. conductor resistance 0.16 Ω /m
Length of cable 4 m
Single wire, cross section 0.14 mm²
Single wire, cross section [AWG] 26
Conductor construction: Number of litz wires: 7
Single wire, material Cu tin-plated
External diameter 8.7 mm
Cable, preassembly Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding no
Outer sheath, material PVC
External sheath, color gray RAL 7035
Environmental conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Flame resistance IEC 60332-1
DIN VDE 0482 Part 332-1
Resistance to oil DIN VDE 0472 Part 803, test type B
Gasoline resistance against occasional splashes
Connector 1
Connection name Field level
Connection method IDC/FLK socket strip
Number of connections 1
Number of positions 34
Pitch 2.54 mm
Connector 2
Connection name Controller level
Connection method IDC/FLK socket strip
Number of connections 1
Number of positions 34
Pitch 2.54 mm
Supported controller
Controller universal
Color code
Connector 1 = connector 2 (optional) = wire color IDC/FLK34 (1) = IDC/FLK34 (1) = black
IDC/FLK34 (2) = IDC/FLK34 (2) = brown
IDC/FLK34 (3) = IDC/FLK34....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLK 34/EZ-DR/ 400/KONFEK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.