

INDUSTRIAL COMPONENT DATA

RPI-BC 107,6 EXT DEV-KIT KMGY 1107460 PHOENIX CONTACT DIN rail housing for Raspberry Pi computers (suitable ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: RPI-BC 107,6 EXT DEV-KIT KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	RPI-BC 107,6 EXT DEV-KIT KMGY
Catalog number	1107460
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-2F9737CDA2
Generated	2026-08-03

Product Overview

DIN rail housing for Raspberry Pi computers (suitable for Raspberry Pi A+, B+, B2, B3, B4); set consisting of lower part, upper part, cover, perfboard, and holder for connecting the HBUS and GPIO strip; housing in accordance with DIN 43880
DIN rail housing for Raspberry Pi computer (suitable for Raspberry Pi A+, B+, B2, B3, B4); set consisting of the bottom, top, cover, perforated frame plates and brackets for the connection of the HBUS and GPIO strip; Housing according to DIN43880

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data
Orderkey 1107460
Packing unit 1
GTIN 4063151008789
Custom tariff number 85366990
Drawings
Dimensions
Ambient conditions
Packaging information

[Classifications](#)

[Item properties](#)

[Material data](#)

[PCB data](#)

[Standards and regulations](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to top](#)[Item properties](#)

[Brief article description](#) Electronic housing

Type RPI-BC 107,6 EXT DEV-KIT KMGY

Order No. 1107460

Housing type DIN rail housing

Type Housing set

Max. IP code to attain IP20

Mounting type Snap in

[Back to top](#)[Dimensions](#)

[Dimensional drawing](#)

Width [w] 107.6 mm

Height [h] 89.7 mm

Depth [d] 62.2 mm

[Back to top](#)[Material data](#)

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polycarbonate

[Back to top](#)[Ambient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

[Back to top](#)[PCB data](#)

Form factor Raspberry Pi

[Back to top](#)[Packaging information](#)

Pieces per package 1

Denomination packing units Pcs.

[Back to top](#)[Standards and regulations](#)

Flammability rating according to UL 94 V0

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)[ETIM](#)

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

[Back to top](#)

ETIM for 1107460 Cabinets and enclosures (EC001031)

Feature Name

Feature Value

Material (EF002169)

Other

Colour (EF000007)

Grey

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RPI-BC 107,6 EXT DEV-KIT KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.