


INDUSTRIAL COMPONENT DATA

RSC 5 CUS 3058144 PHOENIX CONTACT Feed-through terminal block with bolt connection method, cross section: 0...

Brand: PHOENIX CONTACT | Manufacturer Part Number: RSC 5 CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	RSC 5 CUS
Catalog number	3058144
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-463F168596
Generated	2026-08-03

Product Overview

Feed-through terminal block with bolt connection method, cross section: 0.1 - 10 mm², AWG: 26 - 8, width 13 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Feed-through terminal block with bolt connection method, cross section: 0.1 - 10 mm², AWG: 26 - 8, width 13 mm, color: gray

Key Commercial Data

Orderkey 3058144

Packing unit 1

GTIN 4055626290195

Custom tariff number 85369010

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0 27141120

eCl@ss 4.1 27141120

eCI@ss 5.0 27141120

eCI@ss 5.1 27141120

eCI@ss 6.0 27141100

eCI@ss 7.0 27141120

eCI@ss 8.0 27141120

eCI@ss 9.0 27141120

ETIM

ETIM 2.0 EC000897

ETIM 3.0 EC000897

ETIM 4.0 EC000897

ETIM 5.0 EC000897

ETIM 6.0 EC000897

ETIM 7.0 EC000897

UNSPSC

UNSPSC 6.01 30211811

UNSPSC 7.0901 39121410

UNSPSC 11 39121410

UNSPSC 12.01 39121410

UNSPSC 13.2 39121410

ETIM for 3058144 Terminal blocks (EC000897)

Feature Name

Feature Value

Rated current In (EF008250)

57 A

Rated voltage (EF000228)

800 V

Type of electrical connection 1 (EF002526)

Bolt connection

Type of electrical connection 2 (EF002527)

Bolt connection

Number of clamp positions per level (EF002660)

2

Suitable for conductor material (EF012572)

Aluminium/copper

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)

Other

Operating temperature (EF002393)

-60 °C

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

13 mm

Height (EF000040)

53.3 mm

Depth (EF000049)

47.1 mm

Closing plate required (EF002525)

Yes

Colour (EF000007)

Grey

Intern...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RSC 5 CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.