

**INDUSTRIAL COMPONENT DATA**

# RSCWE 6-3/4SL GN 1029997 PHOENIX CONTACT Test terminal strip, nom. voltage: 400 V AC/DC, connection method: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: RSCWE 6-3/4SL GN



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | PHOENIX CONTACT                       |
| MPN / Reference | RSCWE 6-3/4SL GN                      |
| Catalog number  | 1029997                               |
| Category        | Accessories/spare parts for terminals |
| Minimum order   | 1 Pcs                                 |
| Document ID     | EO-BF348D0DA4                         |
| Generated       | 2026-08-03                            |

## Product Overview

Test terminal strip, nom. voltage: 400 V AC/DC, connection method: Ring cable lug, number of connections: 8, number of positions: 4, width: 55.6 mm, height: 80.9 mm, color: green, mounting type: Insertion in base strip

Test pin strip, nominal voltage: 400 V, number of connections: 8, number of poles: 4, connection type: Annular cable terminal, 1st floor, Sizing section: 6 mm<sup>2</sup>, mounting class: Insertion in base strip, color: green

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

## Additional Product Information

Key Commercial Data

Orderkey 1029997

Packing unit 1

Catalog page Page 644 (C-1-2019)

GTIN 4055626532738

Custom tariff number 85366990

Drawings

Dimensions

Mounting

Classifications

[General](#)[Connection data](#)[Standards and Regulations](#)[Drawings](#)[Circuit diagram](#)[Circuit diagram](#)[Back to top](#)[General](#)

Number of positions 4

Number of levels 1

Number of connections 8

Potentials 4

Nominal cross section 6 mm<sup>2</sup>

Color green

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Test surge voltage 5 kV

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.31 W

Maximum load current 30 A (with 10 mm<sup>2</sup> conductor cross section)Current I<sub>th</sub> 24 A

Nominal voltage UN 400 V AC/DC

Open side panel No

[Back to top](#)[Dimensions](#)

Width 55.6 mm

Length 81.9 mm

Height 80.9 mm

Plate thickness 1 mm ... 4 mm

Pitch 8.2 mm

[Back to top](#)[Connection data](#)

Connection 1 level

Connection method Ring cable lug

Screw thread No 8 UNC

Stripping length 12 mm

Tightening torque, min 1.5 Nm

Tightening torque max 1.8 Nm

Connection in acc. with standard IEC 60947-7-1

Conductor cross section flexible min. 0.5 mm<sup>2</sup>Conductor cross section flexible max. 10 mm<sup>2</sup>

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 8

2 conductors with same cross section, solid min. 0.5 mm<sup>2</sup>2 conductors with same cross section, solid max. 6 mm<sup>2</sup>2 conductors with same cross section, stranded min. 0.5 mm<sup>2</sup>

2 conductors with same cross section, stranded...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RSCWE 6-3/4SL GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.