

INDUSTRIAL COMPONENT DATA

SAC-12P-MS/ 0,25-PUR/MR SCO 1530352 PHOENIX CONTACT

Sensor/actuator cable, 12-pole, halogen-free PUR, black ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-12P-MS/ 0,25-PUR/MR SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-12P-MS/ 0,25-PUR/MR SCO
Catalog number	1530352
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-A167F9A1F0
Generated	2026-08-02

Product Overview

Sensor/actuator cable, 12-pole, halogen-free PUR, black RAL 9005, M12 SPEEDCON straight connector, to M12 SPEEDCON angled connector, cable length: 0.25 m

Short Circuit Connector

Sensor/actuator cable, 12-position, Plug straight M12 SPEEDCON, on Plug angled M12 SPEEDCON, cable length: 0.25 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 12

No. of cable outlets 1

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA 6.6
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$?
Insulation resistance $\geq 100 \text{ M}\Omega$?
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 1.5 A
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type Plug straight M12 SPEEDCON
Locking type SPEEDCON
Connection 2
Type Plug angled M12 SPEEDCON
Locking type SPEEDCON
Cable/lineCable length 0.25 m
PUR halogen-free black [PUR]
Dimensional drawing
Shielded no
Cable weight 17 kg/km
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
External cable diameter 7.2 mm
Outer sheath, material PUR
External sheath, color black RAL 9005
Conductor material Tin-plated Cu litz wires
Conductor structure signal line 18x 0.10 mm
AWG signal line 26
Conductor cross section 12x 0.14 mm² (Signal line)
Material wire insulation PP
Wire diameter incl. insulation 1 mm $\pm 0.05 \text{ mm}$ (Signal line)
Single wire, color white, brown, green, yellow, gray, pink, blue, red, black, violet, gray/pink, red/blue
Overall twist 12 wires twisted in layers
Nominal voltag...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-12P-MS/ 0,25-PUR/MR SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.