

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 3,0-936/BP-M12FS 1563452 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 3,0-936/BP-M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 3,0-936/BP-M12FS
Catalog number	1563452
Category	Sensor-actuator patch cord
Minimum order	10 Pcs
Document ID	EO-D3E5AC6951
Generated	2026-08-06

Product Overview

Bus system cable

Bus system cable, PROFINET, 4-pole, PE-X, black RAL 9005, shielded, Straight M12 connector, coding: A, a Built-in mounting female M12, coding: A, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1563452

Packing unit 1 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4046356304481

Weight per Piece (excluding packing) 276.600 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 3 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP68
IP69K
General
Rated current at 40°C 4 A
Rated voltage 250 V
Number of positions 4
Coding A - standard
Signal type/category PROFINET
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA 6.6
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type Ethernet
Cable type (abbreviation) 936
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.95 mm
Wire colors white-blue, orange-yellow
Overall twist Star quad
Shielding Plastic-coated aluminum foil, tinned copper braided shield
Optical shield covering 100 %
External sheath, color black RAL 9005
Outer sheath thickness ≥ 0.8 mm
External cable diameter D 7.25 mm ± 0.3 mm
Minimum bending radius, fixed installation 6 x D
Mini...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 3,0-936/BP-M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.