

INDUSTRIAL COMPONENT DATA

SAC-12P-MS/ 0,8-35T/MS SH SCO 1151536 PHOENIX CONTACT Sensor/actuator cable, 12-pole, PUR/PVC, black RAL 900..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-12P-MS/ 0,8-35T/MS SH SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-12P-MS/ 0,8-35T/MS SH SCO
Catalog number	1151536
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-800144D5E9
Generated	2026-08-04

Product Overview

Sensor/actuator cable, 12-pole, PUR/PVC, black RAL 9005, shielded, M12 SPEEDCON straight connector, coding: A, a M12 SPEEDCON straight connector, coding: A, cable length: 0.8 m
 Sensor/actuator cable, 12-pole, PUR/PVC, black RAL 9005, shielded, Straight male connector M12 SPEEDCON, coding: encoded A, to Straight male connector M12 SPEEDCON, coding: encoded A, cable length: 0.8 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

ETIM for 1151536 Sensors (EC001855)
 Feature Name
 Feature Value
 Number of poles (EF001391)
 12
 Type of electrical connection, field-sided (EF005525)
 M12
 Type of plug-in contact, field sided (EF006269)
 Male (plug)
 Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Male (plug)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

0.8 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

Yes

Cable type (EF000081)

Multi-core

Vulcanize (EF004115)

No

Material contact body (EF008248)

CuZn

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-5 °C

Rated current I_n (EF008250)

1.5 A

Rated voltage (EF000228)

30 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-12P-MS/ 0,8-35T/MS SH SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.