

INDUSTRIAL COMPONENT DATA

SAC-17P-MS/0,2-35T/FS SH SCO 1522844 PHOENIX CONTACT

Sensor/actuator cable, 17 poles, PUR/PVC, black RAL 900..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-17P-MS/0,2-35T/FS SH SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-17P-MS/0,2-35T/FS SH SCO
Catalog number	1522844
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-BC2540ACCB
Generated	2026-08-03

Product Overview

Sensor/actuator cable, 17 poles, PUR/PVC, black RAL 9005, shielded, straight male connector SPEEDCON M12, coded A, in straight female connector, M12-SPEEDCON, cable length: 5 m

Cable for sensors/actuators

Sensor/actuator cable, 17-pos., PUR/PVC, RAL 9005 (black), shielded, straight M12 SPEEDCON male plug (A-coded) to straight M12 SPEEDCON female plug, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 17

Application Standard

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA 6.6
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesContact resistance 0.005 M?
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 1.5 A
Protective circuit unwired
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type Plug straight M12 SPEEDCON
Number of positions 17
Locking type SPEEDCON
Coding type A
Connection 2
Type Socket straight M12 SPEEDCON
Number of positions 17
Locking type SPEEDCON
Coding type A
Cable/lineCable length 0.2 m
Black PUR/PVC twisted pair [35T]
Dimensional drawing
Shielded yes
UL AWM Style 20233 / 1061 (80°C/300 V)
Cable weight 105 kg/km
Cable type Black PUR/PVC twisted pair
Short symbol LSYWC11Y
Cable type (abbreviation) 35T
External cable diameter 9.2 mm ± 0.2 mm
Outer sheath, material PUR
External sheath, color black RAL 9005
Material, inner sheath PVC
Conductor material Tin-plated Cu litz wires
Conductor structure signal line 18x 0.10 mm
AWG signal line 26
Conductor cross section 17x 0.1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-17P-MS/0,2-35T/FS SH SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.