

**INDUSTRIAL COMPONENT DATA**

# SAC-17P-MS/ 1,5-PUR/FS SCO 1409456 PHOENIX CONTACT

## Sensor/actuator cable, 17-pole, halogen-free PUR, black R..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-17P-MS/ 1,5-PUR/FS SCO



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-17P-MS/ 1,5-PUR/FS SCO |
| Catalog number  | 1409456                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-658A99E2E1              |
| Generated       | 2026-08-03                 |

### Product Overview

Sensor/actuator cable, 17-pole, halogen-free PUR, black RAL 9005, M12 SPEEDCON straight connector, coding: A, to M12 SPEEDCON straight female, coding: A, cable length: 1.5 m

Sensor/actuator cable, 17-pole, halogen-free PUR, black RAL 9005, Straight male connector M12 SPEEDCON, coding: A, to Straight connection female M12 SPEEDCON, coding: A, cable length: 1.5 m

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Industrial Field Connectivity (IFC)

### Additional Product Information

ETIM for 1409456 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

17

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Female (bus)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

1.5 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

No

Cable type (EF000081)

Multi-core

Vulcanize (EF004115)

No

Material contact body (EF008248)

CuZn

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-5 °C

Rated current  $I_n$  (EF008250)

1.5 A

Rated voltage (EF000228)

30 V

Degree of protection (IP) (EF005474)

IP65

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-17P-MS/ 1,5-PUR/FS SCO with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.